# S-SERIES 80 MP

























### CERTIFICATIONS















S-SERIES 80 MP	
Cooling capacity (I/h)	80
Max continuos supply (I)	45
Cold water temperature*	5 - 12 °C
Pump	Professional rotary carbonation pump
Cooling technology	Ice bank - single stainless steel coil
Ice bank capacity (I)	14
Ice bank (kg)	5
Condensation	Forced ventilation
Refrigerant gas	R290
Adjustable thermostat	Yes
Supply	230 V - 50 Hz
Compressor power	1/5 HP
Absorbed power	530 W - 2,3 A
Working room temperature	Min 16°C - Max 32°C
Inlet water pipe	Ø5/16" (8 mm)
Inlet CO <sub>2</sub> pipe	Ø5/16" (8 mm)
Dispensing area height (mm)	320
Typology	Countertop
Net weight (kg)	35
Gross weight (kg)	38
Dimensions W x D x H (mm)	360 x 565 x 566
Dispensing options	Cold still water, cold sparkling water
Materials	Robust stainless steel parts Front panel in plexiglass

### OTHER CHARACTERISTICS

Safety inlet valve

Push buttons

Easy access for complete service maintenance

Activated carbon filter inside the machine

## **OPTIONAL**

Water pressure reducer (external)

CO<sub>2</sub> pressure reducer (external)

UV LED OUT (inside) Filters

\* rated at a room temp. of 25 °C and inlet water temp. of 20 °C



Mechanical push buttons in stainless steel

www.R4Brands.com info@R4Brands.com